

EVEGO

# DC EV CHARGERS

Fast. Reliable. Future-Ready



# DC Fast Charger - 14kW / 21kW / 28kW

Designed for Level 2 240V Grid | Universal Compatibility | Fast & Reliable  
- Specifically engineered for the N.A. market, this single phase DC charger is designed for Level 2 240V power grids, ensuring seamless compatibility with all EV models while delivering faster and more stable charging performance.



## EVEGO

Dynamic Load Balancing

SMART METER

POS Payment

VIN/MAC address Charging

Touch Screen

Support OEM & ODM

## PRODUCT PARAMETERS

DC Fast Charger-14kW/21kW/28kW



Model	EVE-W14S-GN1	EVE-W21S-GN1	EVE-W28S-GN1	
<b>Specification Parameter</b>				
<b>Input</b>	Power Supply	L1+L2+PE		
	Power plug	Hardwiring		
	Input Voltage	240V/AC ± 15%		
	Frequency	50/60HZ		
	Efficiency	≥95%		
<b>Output</b>	Output Voltage	200~1000V		
	MAX Output Current	40A	60A	80A
	MAX Output Power	14kW	21kW	28kW
<b>Product Features</b>	Charger Connector	CCS1/CCS2/GBT/CHAdEMO/NACS		
	LED Indicator	RGB LED		
	Display	7 inch touch screen		
	Cable Length	5M (accept customize)		
	E-stop Button	Yes		
	Start Mode	VIN/MAC address Plug&Play/APP/RFID/OCPP		
	OCPP	OCPP 1.6J		
	RFID	Mifare ISO/IEC14443A (Optional)		
	Communication	WIFI/4G/RJ45		
	Installation Method	Wall-Mount		
	<b>Material</b>	Housing Material	Galvanized steel	
Cable Material		TPU		
Energy Meter		Smart Meter		
<b>Safety</b>	RCD	Type A+B AC30mA+DC6mA		
	Protection Class	IP55		
	Impact Protection	IK10		
	Electrical Protection	Over current protection, Short circuit protection, Ground protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection		
	Standby Power	<8W		
	Standard	Safety: UL 2202, UL 2594, UL 2231-1, UL 2231-2, UL 2251, UL 62368-1 Interfaces: SAE J1772, CCS1, ISO 15118-1, ISO 15118-2, DIN 70121 EMC & Radio: FCC Part 15 Subpart B Enclosure & Materials: NEMA 3R, NEMA 4, NEMA 4X, UL 94 Installation: NEC Article 625		
	Warranty	2 Years		
	Certification	TUV CE, RoHS, ETL		
	Cooling	Fan Cooling		
	Noise	≤60dB		
<b>Environment</b>	Work Temperature	-25°C ~+60°C		
	Work Humidity	5%~95%		
	Work Altitude	<2000M		

# DC Fast Charger - 56kW

Designed for Level 2 240V Grid | Universal Compatibility | Fast & Reliable  
 - Specifically engineered for the N.A. market, this single phase DC charger is designed for Level 2 240V power grids, ensuring seamless compatibility with all EV models while delivering faster and more stable charging performance.



## EVEGO

 Dynamic Load Balancing

 SMART METER

 POS Payment

 VIN/MAC address Charging

 Touch Screen

 Support OEM & ODM

## PRODUCT PARAMETERS

US DC Fast Charger-56kW



Model	EVE-F56D-GN1		
<b>Specification Parameter</b>			
<b>Input</b>	Power Supply	L1+L2+PE	
	Power plug	Hardwiring	
	Input Voltage	240V/AC ± 15%	
	Frequency	50/60HZ	
	Efficiency	≥95%	
<b>Output</b>	Output Voltage	200~1000V	
	MAX Output Current	160A	
	MAX Output Power	56kW	
<b>Product Features</b>	Charger Connector	CCS1/CCS2/GBT/CHAdEMO/NACS	
	LED Indicator	RGB LED	
	Display	10.1 inch touch screen	
	Cable Length	5M (accept customize)	
	E-stop Button	Yes	
	Start Mode	VIN/MAC address Plug&Play/APP/RFID/OCPP	
	OCPP	OCPP 1.6J	
	RFID	Mifare ISO/IEC14443A (Optional)	
	Communication	WIFI/4G/RJ45	
	Installation Method	Floor-Standing	
<b>Material</b>	Housing Material	Galvanized steel	
	Cable Material	TPU	
	Energy Meter	Smart Meter	
<b>Safety</b>	RCD	Type A+B AC30mA+DC6mA	
	Protection Class	IP55	
	Impact Protection	IK10	
	Electrical Protection	Over current protection, Short circuit protection, Ground protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection	
	Standby Power	<8W	
	Standard	Safety: UL 2202, UL 2594, UL 2231-1, UL 2231-2, UL 2251, UL 62368-1 Interfaces: SAE J1772, CCS1, ISO 15118-1, ISO 15118-2, DIN 70121 EMC & Radio: FCC Part 15 Subpart B Enclosure & Materials: NEMA 3R, NEMA 4, NEMA 4X, UL 94 Installation: NEC Article 625	
	Warranty	2 Years	
	Certification	TUV CE, RoHS, ETL	
	<b>Environment</b>	Cooling	Fan Cooling
		Noise	≤60dB
Work Temperature		-25℃~+60℃	
Work Humidity		5%~95%	
Work Altitude	<2000M		

# DC Fast Charger- DC18kW /36kW

Designed for threes phases 208V Grid | Universal Compatibility | Fast & Reliable

- Efficient DCDC conversion, direct battery power supply.
- No need for traditional AC-DC conversion—DC-DC architecture reduces energy loss, improves efficiency, and delivers direct power to the EV batter.



## EVEGO

Dynamic Load Balancing

SMART METER

POS Payment

VIN/MAC address Charging

Touch Screen

Support OEM & ODM

## PRODUCT PARAMETERS

DC Fast Charger- DC18kw



Model	EVE-W18S-GN2	EVE-W36S-GN2
<b>Specification Parameter</b>		
<b>Input</b>	Power Supply	L1+L2+L3+N+PE
	Power plug	Hardwiring
	Input Voltage	208V/AC ± 15%
	Frequency	50/60HZ
	Efficiency	≥95%
<b>Output</b>	Output Voltage	200~1000V
	MAX Output Current	200A
	MAX Output Power	18kW / 36kW
<b>Product Features</b>	Charger Connector	CCS1/CCS2/GBT/CHAdeMO/NACS
	LED Indicator	RGB LED
	Display	7 inch touch screen
	Cable Length	5M (accept customize)
	E-stop Button	Yes
	Start Mode	VIN/MAC address Plug&Play/APP/RFID/OCPP
	OCPP	OCPP 1.6J
	RFID	Mifare ISO/IEC14443A (Optional)
	Communication	WIFI/4G/RJ45
	Installation Method	Wall-Mount
<b>Material</b>	Housing Material	Galvanized steel
	Cable Material	TPU
<b>Safety</b>	Energy Meter	Smart Meter
	RCD	Type A+B AC30mA+DC6mA
	Protection Class	IP55
	Impact Protection	IK10
	Electrical Protection	Over current protection, Short circuit protection, Ground protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection
	Standby Power	<8W
	Standard	Safety: UL 2202, UL 2594, UL 2231-1, UL 2231-2, UL 2251, UL 62368-1 Interfaces: SAE J1772, CCS1, ISO 15118-1, ISO 15118-2, DIN 70121 EMC & Radio: FCC Part 15 Subpart B Enclosure & Materials: NEMA 3R, NEMA 4, NEMA 4X, UL 94 Installation: NEC Article 625
<b>Environment</b>	Warranty	2 Years
	Certification	TUV CE, RoHS, ETL
	Cooling	Fan Cooling
	Noise	≤60dB
	Work Temperature	-25℃~+60℃
	Work Humidity	5%~95%
Work Altitude	<2000M	

# DC Fast Charger - 20/30/40kW

- Ultra Portable Compact design, easy to carry and store.
- Fast DC Charging Rapid charging to keep you moVIN/MAC addressg.
- Universal Compatibility Works seamlessly with most EV models.



EVEGO



Dynamic Load Balancing

SMART METER

POS Payment

VIN/MAC address Charging

Touch Screen

Support OEM & ODM

## PRODUCT PARAMETERS

US DC Fast Charger - 20/30/40kW



Model	EVE-M20S-GN3	EVE-M30S-GN3	EVE-M40S-GN3	
<b>Specification Parameter</b>				
<b>Input</b>	Power Supply	L1+L2+L3+N+PE		
	Power plug	Hardwiring		
	Input Voltage	480VAC ± 10%		
	Frequency	50/60HZ		
	Efficiency	≥95%		
<b>Output</b>	Output Voltage	200~1000V		
	MAX Output Current	67A	100A	133A
	MAX Output Power	20kW	30kW	40kW
<b>Product Features</b>	Charger Connector	CCS1/CCS2/GBT/CHAdEMO/NACS		
	LED Indicator	RGB LED		
	Display	4.3inch touch screen		
	Cable Length	5M (accept customize)		
	E-stop Button	Yes		
	Start Mode	VIN/MAC address Plug&Play/APP/RFID/OCPP		
	OCPP	OCPP 1.6J		
	RFID	Mifare ISO/IEC14443A (Optional)		
	Communication	WIFI/4G/RJ45		
	Installation Method	Mobile		
	Housing Material	Galvanized steel		
<b>Material</b>	Cable Material	TPU		
	Energy Meter	Smart Meter		
<b>Safety</b>	RCD	Type A+B AC30mA+DC6mA		
	Protection Class	IP55		
	Impact Protection	IK10		
	Electrical Protection	Over current protection, Short circuit protection, Ground protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection		
	Standby Power	<8W		
	Standard	Safety: UL 2202, UL 2594, UL 2231-1, UL 2231-2, UL 2251, UL 62368-1 Interfaces: SAE J1772, CCS1, ISO 15118-1, ISO 15118-2, DIN 70121 EMC & Radio: FCC Part 15 Subpart B Enclosure & Materials: NEMA 3R, NEMA 4, NEMA 4X, UL 94 Installation: NEC Article 625		
	Warranty	2 Years		
	Certification	TUV CE, RoHS, ETL		
	Cooling	Fan Cooling		
	Noise	≤60dB		
<b>Environment</b>	Work Temperature	-25°C~+60°C		
	Work Humidity	5%~95%		
	Work Altitude	<2000M		

# DC Fast Charger - 30/40/60kW

- Dual guns DC EV charger.
- Compared to floor standing chargers, the wall mounted design saves space, making it ideal for commercial and residential settings with limited parking.
- Compact and efficient, suitable for various scenarios.
- Wall mounted design saves space, making it ideal for commercial parking lots, corporate charging stations, and more.



**EVEGO**

Dynamic Load Balancing

SMART METER

POS Payment

VIN/MAC address Charging

Touch Screen

Support OEM & ODM

## PRODUCT PARAMETERS

DC Fast Charger-30/40/60kW



Model	EVE-W30D-GN3	EVE-W40D-GN3	EVE-W60D-GN3	
<b>Specification Parameter</b>				
<b>Input</b>	Power Supply	L1+L2+L3+N+PE		
	Power plug	Hardwiring		
	Input Voltage	480VAC ± 10%		
	Frequency	50/60HZ		
	Efficiency	≥95%		
<b>Output</b>	Output Voltage	200~1000V		
	MAX Output Current	100A	125A	200A
	MAX Output Power	30kW	40kW	60kW
<b>Product Features</b>	Charger Connector	CCS1/CCS2/GBT/CHAdemo/NACS		
	LED Indicator	RGB LED		
	Display	7inch touch screen		
	Cable Length	5M (accept customize)		
	E-stop Button	Yes		
	Start Mode	VIN/MAC address Plug&Play/APP/RFID/OCPP		
	OCPP	OCPP 1.6J		
	RFID	Mifare ISO/IEC14443A (Optional)		
	Communication	WIFI/4G/RJ45		
	Installation Method	Wall-Mount		
	<b>Material</b>	Housing Material	Galvanized steel	
Cable Material		TPU		
<b>Safety</b>	Energy Meter	Smart Meter		
	RCD	Type A+B AC30mA+DC6mA		
	Protection Class	IP55		
	Impact Protection	IK10		
	Electrical Protection	Over current protection, Short circuit protection, Ground protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection		
	Standby Power	<8W		
	Standard	Safety: UL 2202, UL 2594, UL 2231-1, UL 2231-2, UL 2251, UL 62368-1 Interfaces: SAE J1772, CCS1, ISO 15118-1, ISO 15118-2, DIN 70121 EMC & Radio: FCC Part 15 Subpart B Enclosure & Materials: NEMA 3R, NEMA 4, NEMA 4X, UL 94 Installation: NEC Article 625		
	Warranty	2 Years		
	Certification	TUV CE, RoHS, ETL		
	<b>Environment</b>	Cooling	Fan Cooling	
Noise		≤60dB		
Work Temperature		-25℃~+60℃		
Work Humidity		5%~95%		
Work Altitude		<2000M		

# DC Fast Charger - 60/80kW

- OCPP smart management for efficient operation.
- OCPP protocol support enables remote monitoring, smart scheduling, and billing management.



EVEGO



Dynamic Load Balancing

SMART METER

POS Payment

VIN/MAC address Charging

Touch Screen

Support OEM & ODM

## PRODUCT PARAMETERS

DC Fast Charger-60/80kW



Model	EVE-F60D-GN3	EVE-F80D-GN3
<b>Specification Parameter</b>		
<b>Input</b>	Power Supply	L1+L2+L3+N+PE
	Power plug	Hardwiring
	Input Voltage	480VAC ± 10%
	Frequency	50/60HZ
	Efficiency	≥95%
<b>Output</b>	Output Voltage	200~1000V
	MAX Output Current	200A
	MAX Output Power	60kW
<b>Product Features</b>	Charger Connector	CCS1/CCS2/GBT/CHAdeMO/NACS double gun
	LED Indicator	RGB LED
	Display	10.1inch touch screen
	Cable Length	5M (accept customize)
	E-stop Button	Yes
	Start Mode	VIN/MAC address Plug&Play/APP/RFID/OCPP
	OCPP	OCPP 1.6J
	RFID	Mifare ISO/IEC14443A (Optional)
	Communication	WIFI/4G/RJ45
	Installation Method	Floor-Standing
	<b>Material</b>	Housing Material
Cable Material		TPU
Energy Meter		Smart Meter
<b>Safety</b>	RCD	Type A+B AC30mA+DC6mA
	Protection Class	IP55
	Impact Protection	IK10
	Electrical Protection	Over current protection, Short circuit protection, Ground protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection
	Standby Power	<8W
	Standard	Safety: UL 2202, UL 2594, UL 2231-1, UL 2231-2, UL 2251, UL 62368-1 Interfaces: SAE J1772, CCS1, ISO 15118-1, ISO 15118-2, DIN 70121 EMC & Radio: FCC Part 15 Subpart B Enclosure & Materials: NEMA 3R, NEMA 4, NEMA 4X, UL 94 Installation: NEC Article 625
	Warranty	2 Years
<b>Environment</b>	Certification	TUV CE, RoHS, ETL
	Cooling	Fan Cooling
	Noise	≤60dB
	Work Temperature	-25°C ~+60°C
	Work Humidity	5%~95%
Work Altitude	<2000M	

# DC Fast Charger - 120-240kW

- OCPP smart management for efficient operation
- OCPP protocol support enables remote monitoring, smart scheduling, and billing management.



**EVEGO**

Dynamic Load Balancing

SMART METER

POS Payment

VIN/MAC address Charging

Touch Screen

Support OEM & ODM

## PRODUCT PARAMETERS

DC Fast Charger - 120-240kW



Model	EVE-F120D-GN3	EVE-F160D-GN3	EVE-F180D-GN3	EVE-F240D-GN3	
<b>Specification Parameter</b>					
<b>Input</b>	Power Supply	L1+L2+L3+N+PE			
	Power plug	Hardwiring			
	Input Voltage	480VAC ± 10%			
	Frequency	50/60HZ			
	Efficiency	≥95%			
<b>Output</b>	Output Voltage	200~1000V			
	MAX Output Current	250V		300A	
	MAX Output Power	120kW	160kW	180kW	240kW
<b>Product Features</b>	Charger Connector	CCS1/CCS2/GBT/CHAdeMO/NACS double gun			
	LED Indicator	RGB LED			
	Display	10.1inch touch screen			
	Cable Length	5M (accept customize)			
	E-stop Button	Yes			
	Start Mode	VIN/MAC address Plug&Play/APP/RFID/OCPP			
	OCPP	OCPP 1.6J			
	RFID	Mifare ISO/IEC14443A (Optional)			
	Communication	WIFI/4G/RJ45			
	Installation Method	Floor-Standing			
<b>Material</b>	Housing Material	Galvanized steel			
	Cable Material	TPU			
	Energy Meter	Smart Meter			
<b>Safety</b>	RCD	Type A+B AC30mA+DC6mA			
	Protection Class	IP55			
	Impact Protection	IK10			
	Electrical Protection	Over current protection, Short circuit protection, Ground protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection			
	Standby Power	<8W			
	Standard	Safety: UL 2202, UL 2594, UL 2231-1, UL 2231-2, UL 2251, UL 62368-1 Interfaces: SAE J1772, CCS1, ISO 15118-1, ISO 15118-2, DIN 70121 EMC & Radio: FCC Part 15 Subpart B Enclosure & Materials: NEMA 3R, NEMA 4, NEMA 4X, UL 94 Installation: NEC Article 625			
	Warranty	2 Years			
	Certification	TUV CE, RoHS, ETL			
	<b>Environment</b>	Cooling	Fan Cooling		
		Noise	≤60dB		
Work Temperature		-25°C ~ +60°C			
Work Humidity		5%~95%			
Work Altitude	<2000M				

# DC Fast Charger - 240-480kW

- Ultra fast charging, reduced waiting time.
- Up to 240kW DC fast charging significantly reduces charging time and improves station turnover.



**EVEGO**

Dynamic Load Balancing

SMART METER

POS Payment

VIN/MAC address Charging

Touch Screen

Support OEM & ODM

## PRODUCT PARAMETERS

DC Fast Charger - 240-480kW



Model	EVE-F240D-GN3	EVE-F360D-GN3	EVE-F480D-GN3
<b>Specification Parameter</b>			
<b>Input</b>	Power Supply	L1+L2+L3+N+PE	
	Power plug	Hardwiring	
	Input Voltage	480VAC ± 10%	
	Frequency	50/60HZ	
	Efficiency	≥95%	
<b>Output</b>	Output Voltage	200~1000V	
	MAX Output Current	300A air-cooled, 600A liquid-cooled	
	MAX Output Power	240kW	360kW
<b>Product Features</b>	Charger Connector	CCS1/CCS2/GBT/CHAdeMO/NACS double gun	
	LED Indicator	RGB LED	
	Display	10.1inch touch screen	
	Cable Length	5M (accept customize)	
	E-stop Button	Yes	
	Start Mode	VIN/MAC address Plug&Play/APP/RFID/OCPP	
	OCPP	OCPP 1.6J	
	RFID	Mifare ISO/IEC14443A (Optional)	
	Communication	WIFI/4G/RJ45	
	Installation Method	Floor-Standing	
	Housing Material	Galvanized steel	
<b>Material</b>	Cable Material	TPU	
	Energy Meter	Smart Meter	
<b>Safety</b>	RCD	Type A+B AC30mA+DC6mA	
	Protection Class	IP55	
	Impact Protection	IK10	
	Electrical Protection	Over current protection, Short circuit protection, Ground protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection	
	Standby Power	<8W	
	Standard	Safety: UL 2202, UL 2594, UL 2231-1, UL 2231-2, UL 2251, UL 62368-1 Interfaces: SAE J1772, CCS1, ISO 15118-1, ISO 15118-2, DIN 70121 EMC & Radio: FCC Part 15 Subpart B Enclosure & Materials: NEMA 3R, NEMA 4, NEMA 4X, UL 94 Installation: NEC Article 625	
	Warranty	2 Years	
	Certification	TUV CE, RoHS, ETL	
	Cooling	Fan Cooling	
	Noise	≤60dB	
<b>Environment</b>	Work Temperature	-25℃~+60℃	
	Work Humidity	5%~95%	
	Work Altitude	<2000M	

# DC Advertising Fast Charger - 120-240kW

- 55" advertising screen generates revenue while charging.
- One unit, dual benefits — boosting site value and ROI.



**EVEGO**

Dynamic Load Balancing

SMART METER

POS Payment

VIN/MAC address Charging

Touch Screen

Support OEM & ODM

## PRODUCT PARAMETERS

DC Advertising Fast Charger - 120-240kW



Model	EVE-FA120D-GN3	EVE-FA160D-GN3	EVE-FA180D-GN3	EVE-FA240D-GN3
<b>Specification Parameter</b>				
<b>Input</b>	Power Supply	L1+L2+L3+N+PE		
	Power plug	Hardwiring		
	Input Voltage	480VAC ± 10%		
	Frequency	50/60HZ		
	Efficiency	≥95%		
<b>Output</b>	Output Voltage	200~1000V		
	MAX Output Current	250V		300A
	MAX Output Power	120kW	160kW	180kW
<b>Product Features</b>	Charger Connector	CCS1/CCS2/GBT/CHAdeMO/NACS double gun		
	LED Indicator	RGB LED		
	Display	55 inch Advertising screen		
	Cable Length	5M (accept customize)		
	E-stop Button	Yes		
	Start Mode	VIN/MAC address Plug&Play/APP/RFID/OCPP		
	OCPP	OCPP 1.6J		
	RFID	Mifare ISO/IEC14443A (Optional)		
	Communication	WIFI/4G/RJ45		
	Installation Method	Floor-Standing		
	<b>Material</b>	Housing Material	Galvanized steel	
Cable Material		TPU		
Energy Meter		Smart Meter		
<b>Safety</b>	RCD	Type A+B AC30mA+DC6mA		
	Protection Class	IP55		
	Impact Protection	IK10		
	Electrical Protection	Over current protection, Short circuit protection, Ground protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection		
	Standby Power	<8W		
	Standard	Safety: UL 2202, UL 2594, UL 2231-1, UL 2231-2, UL 2251, UL 62368-1 Interfaces: SAE J1772, CCS1, ISO 15118-1, ISO 15118-2, DIN 70121 EMC & Radio: FCC Part 15 Subpart B Enclosure & Materials: NEMA 3R, NEMA 4, NEMA 4X, UL 94 Installation: NEC Article 625		
	Warranty	2 Years		
	Certification	TUV CE, RoHS, ETL		
	Cooling	Fan Cooling		
	Noise	≤60dB		
<b>Environment</b>	Work Temperature	-25°C ~+60°C		
	Work Humidity	5%~95%		
	Work Altitude	<2000M		

# Super Charging Station – Flexible and Efficient Power Distribution – 360/720/960kW

- Flexible setup: Supports 360kW / 720kW / 960kW combinations to fit different needs.
- Smart power sharing: Multiple posts can share power dynamically, charging several cars efficiently at once.
- Wide compatibility: Works with CCS1, CCS2, GB/T, CHAdeMO, and NACS, covering global vehicle standards.
- Modular design: Main unit + posts, easy to install, maintain, and expand when needed.



**EVEGO**

Dynamic Load Balancing

SMART METER

POS Payment

VIN/MAC address Charging

Touch Screen

Support OEM & ODM

## PRODUCT PARAMETERS

Super Charging Station – Flexible and Efficient Power Distribution – 360/720/960kW



Model	EVE-SC360D-GN3	EVE-SC720D-GN3	EVE-SC960D-GN3	
<b>Specification Parameter</b>				
<b>Input</b>	Power Supply	L1+L2+L3+N+PE		
	Power plug	Hardwiring		
	Input Voltage	480VAC ± 10%		
	Frequency	50/60HZ		
	Efficiency	≥95%		
<b>Output</b>	Output Voltage	200~1000V		
	MAX Output Current	250V		
	MAX Output Power	360kW	720kW	960kW
	POST	1 POST	2 POSTs	3 POSTs
	Load Sharing	Dynamic Sharing		
<b>Product Features</b>	Charger Connector	CCS1/CCS2/GBT/CHAdeMO/NACS double gun		
	LED Indicator	RGB LED		
	Display	10.1inch touch screen		
	Cable Length	5M (accept customize)		
	E-stop Button	Yes		
	Start Mode	VIN/MAC address Plug&Play/APP/RFID/OCPP		
	OCPP	OCPP 1.6J		
	RFID	Mifare ISO/IEC14443A (Optional)		
	Communication	WIFI/4G/RJ45		
	Installation Method	Floor-Standing		
	Housing Material	Galvanized steel		
	Cable Material	TPU		
<b>Material</b>	Energy Meter	Smart Meter		
	RCD	Type A+B AC30mA+DC6mA		
	Protection Class	IP55		
	Impact Protection	IK10		
	Electrical Protection	Over current protection, Short circuit protection, Ground protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection		
	Standby Power	<8W		
	Standard	Safety: UL 2202, UL 2594, UL 2231-1, UL 2231-2, UL 2251, UL 62368-1 Interfaces: SAE J1772, CCS1, ISO 15118-1, ISO 15118-2, DIN 70121 EMC & Radio: FCC Part 15 Subpart B Enclosure & Materials: NEMA 3R, NEMA 4, NEMA 4X, UL 94 Installation: NEC Article 625		
	Warranty	2 Years		
	Certification	TUV CE, RoHS, ETL		
	Cooling	Fan Cooling		
Noise	≤60dB			
<b>Environment</b>	Work Temperature	-25°C ~+60°C		
	Work Humidity	5%~95%		
	Work Altitude	<2000M		